REFRIGERATOR MANUFACTURER
Turbo air
more durable, efficient, beautiful

4184 E. Conant St.
Long Beach, CA 90808
Tel. 310-900-1000
Fax. 310-900-1077
www.turboairinc.com

Project :	
Model # :	
Item # :	Qty :
Available W/H :	
Approval :	

Sandwich / Salad Unit

Food Prep Tables
J Series

Model : JST-72

FEATURES & BENEFITS

- ***Hot gas condensate system*** **Only Turbo Air models**
  Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

- ***Side mount compressor unit***
  By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to provide high efficiency in narrow spaces.

- ***Efficient refrigeration system***
  Turbo Air J series refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

- ***9-1/2" deep, 1/2" thick cutting board included with convenient side rail***

- ***Exterior & interior of the cabinet***
  The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

- ***High-density polyurethane insulation***
  The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- ***Ergonomically designed doors***
  Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

- ***Adjustable, heavy duty, PE (polyethylene) coated wire shelves***

- ***Magnetic door gaskets***
  Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

- ***Refrigerator holds 33°F ~ 39°F for the best in food preservation***

Intertek Intertek ISO9001:2008 2 YEAR PARTS AND LABOR WARRANTY Compressor 5 YEAR WARRANTY (U.S.A only)

Model	Swing Door	CU./FT.	#of Shelves	#of Pans	#of Hood	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
JST-72	3	18	3	18	2	1/4	4.8	275	70 7/8 x 27 1/2 x 35 3/4

Ver.201601

* Depth does not include 1-1/2" for cutting boards and 1" for rear spacers. † Height does not include 5" for caster height.

Sandwich / Salad Unit

Food Prep Tables
J Series

Model : JST-72

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	NEMA 5-15P
Full Load Amperes	4.8
Compressor HP	1/4
Cord Length (ft.)	9
Refrigerant	R-134A
DIMENSIONAL DATA	
Ext. Length Overall (in.)	70 7/8 (1800mm)
Ext. Depth Overall (in.)*	27 1/2 (698mm)
Ext. Height Overall (in.)†	35 3/4 (908mm)
# of Doors	3
# of Shelves	3
# of Pans	18
Net Capacity (cu. ft.)	18
Net Weight (lbs.)	254
Gross Weight (lbs.)	275
Shelf Size (in.)	17 1/4 x 17 3/4 (Left/Right)
	19 1/2 x 17 3/4 (Middle)

Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Depth does not include 1-1/2" for cutting boards and 1" for rear spacers.
† Height does not include 5" for caster height.

- **WARRANTY : 2 Year Parts and Labor Warranty**
  Additional 3 Year Warranty on Compressor

- ***Self-contained system***
- ***Standard 4" dia. swivel casters with locks on the front set***
- ***Standard 1/6 size, 4" deep condiment pans included***
- ***2.5" dia. casters available (optional)***
- ***Legs available (optional)***

- **OPTIONAL ACCESSORIES :**
  - ❑ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
  - ❑ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
  - ❑ 6" ABS plastic leg: 30221M0200
  - ❑ 6" stainless steel leg: 30221M0600
  - ❑ Additional PE coated wire shelf: BR89000102 (Left/Right), BR99000102 (Middle)

- **Door lock: extra lead time will apply, please call factory for more details to order**

PLAN VIEW

(unit : inch)



PLAN VIEW



SIDE VIEW

Ver.201601

- **Turbo Air** : 800-627-0032
- **GK** : 800-500-3519
- **Warranty** : 800-381-7770
- **AC** : 888-900-1002